MAW 905 L



Salient Features

Ideal tyre for modern farming

Low section implement tyres offering high load capacity with minimum soil compaction

Suitable for both on and off road applications

Applications

Baler	Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD (LLV)		INFLATION PRESSURE	LI/SS	MAX. LOAD (HLV)		INFLATION PRESSURE
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	(bar)		30KMPH (Kgs)	40KMPH (Kgs)	(bar)
15.0/55-17	10	TL	13.0	13.0	850	391	379	2491	134A6 / 130A8	2120	1900	2.6	141A6 / 137A8	2575	2300	3.1
15.0/55-17	12	TL	13.0	13.0	850	391	379	2491	138A6 / 134A8	2360	2120	3.1	144A6 / 140A8	2800	2500	3.7
15.0/55-17	14	TT/TL	13.0	13.0	850	391	379	2491	141A6 / 137A8	2575	2300	3.7	147A6 / 143A8	3075	2725	4.9
15.0/55-17	18	TL	13.0	13.0	850	391	379	2491	146A6 / 142A8	3000	2650	4.4	152A6 / 148A8	3550	3150	5.3