MAW 977



Salient Features

Ideal tyre for modern farming

Low section implement tyres offering high load capacity with minimum soil compaction

Suitable for both on and off road applications

Applications

Baler	Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD (LLV)		INFLATION PRESSURE	LI/SS	MAX. LOAD (HLV)		INFLATION PRESSURE
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	(bar)		30KMPH (Kgs)	40KMPH (Kgs)	(bar)
400/60-15.5	12	TL	AG13	–	874	404	380	2561	142A6/138A8	2650	2360	3.1	148A6/144A8	3150	2800	3.8
400/60-15.5	14	TL	AG13	–	874	404	380	2561	145A6/141A8	2900	2575	3.6	151A6/148A8	3450	3150	4.4
400/60-15.5	16	TL	AG13	–	874	404	380	2561	147A6/143A8	3075	2725	4.3	153A6/149A8	3650	3250	5.2
400/60-15.5	18	TL	AG13	–	874	404	380	2561	149A6/145A8	3250	2900	5.1	155A6/151A8	3875	3450	6.1
19.0/45-17	10	TL	16	–	852	491	380	2530	138A6/134A8	2360	2120	2.3	144A6/140A8	2800	2500	2.7
19.0/45-17	14	TL	16	–	852	491	380	2530	144A6/140A8	2800	2500	2.8	150A6/146A8	3350	3000	3.4
19.0/45-17	16	TL	16	–	852	491	380	2530	149A6/145A8	3250	2900	3.5	155A6/151A8	3875	3450	4.2
19.0/45-17	18	TL	16	–	852	491	380	2530	154A6/150A8	3750	3350	3.8	160A6/156A8	4500	4000	4.6
500/50-17	10	TL	16	–	965	495	406	2712	143A6/139A8	2725	2430	2	149A6/145A8	3250	2900	2.4
500/50-17	14	TL	16	–	965	495	406	2712	149A6/145A8	3250	2900	2.8	155A6/151A8	3875	3450	3.4
500/50-17	16	TL	16	–	965	495	406	2712	152A6/148A8	3550	3150	3.5	158A6/154A8	4250	3750	4.2
500/50-17	18	TL	16	–	965	495	406	2712	154A6/150A8	3750	3350	4.2	160A6/156A8	4500	4000	5