



## Salient Features

Multi-angled and bold lug-bars for service durability and self cleaning.  
 Suitably designed lug bar spacing for comfort drive & added traction.  
 Strong and sturdy body plies for longer service durability.  
 Tread contact patch with broader lugs for heavy duty prime-movers.

## Applications

Irrigator

## SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
11.2-24	4	TT/TL	W 10	W 9	1090	284	515	3200	101 A6 / 98 A8	825	750	1.2
11.2-24	6	TT/TL	W 10	W 9	1090	284	515	3200	110 A6 / 106 A8	1060	950	1.8
11.2-24	8	TT	W 10	W 9	1090	284	515	3200	116 A6 / 112 A8	1250	1120	2.4
11.2-38	4	TT/TL	W 10	W 9	1445	284	686	4242	109 A6 / 104 A8	1030	900	1.3
11.2-38	6	TT/TL	W 10	W 9	1445	284	686	4242	117 A6 / 113 A8	1285	1150	1.8
11.2-38	8	TT	W 10	W 9	1445	284	686	4242	122 A6 / 118 A8	1500	1320	2.4