MRT 329



Salient Features

Specially designed bias tyre for Row Crop

No damage to the crops, preserving the yield

Self-cleaning properties

Applications

2WD Tractor	4WD Tractor	MFWA

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	(bar)
4.50-19	6	TT	3.0	–	736	122	339	2171	83A6 / 79A8	487	437	4.4
4.00-21	6	TT	3.0	–	765	115	352	2257	48A6 / 44A8	180	160	1.8
5.00-21	–	–	–	–	–	–	–	–	–	–	–	–
8.3-28	8	TT	W7	W6	1104	213	523	3246	103A6 / 99A8	875	775	2.4
4.00-30	6	TT	3.0	–	995	117	458	2935	72A6 / 68A8	355	315	2.3
7.20-30	6	TT	6.0	–	1095	183	510	3230	95A6 / 91A8	690	615	2.3
9.50-30	6	TT	8.0	–	1200	241	552	3540	115A6 / 111A8	1215	1090	2.8
8.3-32	6	TT	W 7	–	1195	211	572	3585	105 A6 / 101 A8	925	825	2.4
8.3-32	8	TT	W 7	–	1195	211	572	3585	111 A6 / 107 A8	1090	975	3.2
9.5-32	6	TT	W 8	W 7	1255	235	594	3686	110 A6 / 106 A8	1060	950	2.1
9.5-32	8	TT	W 8	W 7	1255	235	594	3686	116 A6 / 112 A8	1250	1120	2.8
9.5-32	12	TT	W 8	W 7	1255	235	594	3686	125 A6 / 121 A8	1650	1450	4.1
4.00-36	8	TT	3.0	–	1140	120	524	3363	74A6 / 70A8	375	335	2.3
4.50-36	10	TT	3.0	–	1150	135	529	3393	80A6 / 76A8	450	400	2.4
5.00-36	12	TT	3.0	–	1175	145	541	3466	81A6 / 77A8	462	412	2.5
7.2-36	8	TT	6.0	–	1255	183	577	3702	108 A6 / 104 A8	1000	900	3.7
7.2-36	12	TT	6.0	–	1255	183	577	3702	112A6 / 108A8	1120	1000	4.5
8.3-36	6	TT	7.0	–	1295	211	596	3820	107 A6 / 103 A8	975	875	2.4
8.3-36	8	TT	7.0	–	1295	211	596	3820	113 A6 / 109 A8	1150	1030	3.2
8.3-36	14	TT	7.0	–	1295	211	596	3820	120A6 / 116A8	1400	1250	4.5
9.5-36	6	TT	8.0	–	1355	241	623	3997	113A6 / 109A8	1150	1030	2.1

MRT 329

9.5-36	8	TT	8.0	–	1355	241	623	3997	118 A6 / 114 A8	1360	1180	2.8
9.5-36	10	TT	8.0	–	1355	241	623	3997	122A6 / 118A8	1500	1320	3.5
9.5-36	14	TT	8.0	–	1355	241	623	3997	128A6 / 124A8	1800	1600	4.7
8.3-38	8	TT	7.0	–	1350	211	621	3983	116 A6 / 112 A8	1250	1120	3.5
11.2-38	8	TT	10.0	–	1465	284	674	4322	117 A6 / 113 A8	1285	1150	2.4