MRT 330



Salient Features

Multi-angled curved lug-bars for improved traction and self-cleaning.

Rugged design for excellent traction in both dry and wet soil conditions.

Longer continuity of lug bars in contact patch for comfort driving.

Strong and sturdy body plies for longer service durability even on haulage.

Cut and crack resistant tread compound for longer service life.

Applications

2WD Tractor	4WD Tractor	MFWA

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	(bar)
8.00-18	8	TT	W7	W5.50F	845	190	390	2515	98 A6 / 96 A8	750	710	2.1
12.4-28	8	TT	W 11	W 9, W 10	1270	315	589	3805	123 A6 / 120 A8	1550	1400	2.3
12.4-28	10	TT	W 11	W 9, W 10	1270	315	589	3805	124 A6 / 120 A8	1600	1400	2.4
12.4-28	12	TT	W 11	W 9, W 10	1270	315	589	3805	125 A6 / 121 A8	1650	1450	2.5
12.4-28	14	TT	W 11	W 9, W 10	1270	315	589	3805	126 A6 / 122 A8	1700	1500	2.6
13.6-28	8	TT	W 12	W 11	1310	345	610	3851	125 A6 / 121 A8	1650	1450	2.0
13.6-28	10	TT	W 12	W 11	1310	345	610	3851	127 A6/ 123 A8	1750	1550	2.2
13.6-28	12	TT	W 12	W 11	1310	345	610	3851	128A6/ 124A8	1800	1600	2.3
13.6-28	14	TT	W 12	W 11	1310	345	610	3851	129A6/ 125A8	1850	1650	2.4
14.9-28	8	TT	W 13	W 11, W 12	1365	378	634	4013	130 A6 / 126 A8	1900	1700	1.8
14.9-28	10	TT	W 13	W 11, W 12	1365	378	634	4013	132 A6 / 128 A8	2000	1800	2.1
14.9-28	12	TT	W 13	W 11, W 12	1365	378	634	4013	134 A6 / 130 A8	2120	1900	2.3
14.9-28	14	TT/TL	W 13	W 11, W 12	1365	378	634	4013	136 A6 / 132 A8	2240	2000	2.6
16.9-28	8	TT/TL	W 15 L	W 14 L	1435	429	655	4310	135 A6 / 131 A8	2180	1950	1.7
16.9-28	10	TT/TL	W 15 L	W 14 L	1435	429	655	4310	139 A6 / 135 A8	2430	2180	2.0
16.9-28	12	TT/TL	W 15 L	W 14 L	1435	429	655	4310	143 A6 / 139 A8	2725	2430	2.4
16.9-28	14	TT/TL	W 15 L	W 14 L	1435	429	655	4310	146 A6 / 142 A8	3000	2650	2.8
16.9-30	8	TT	W 15 L	W 14 L	1485	429	685	4381	137 A6 / 132 A8	2300	2000	1.7
16.9-30	10	TT	W 15 L	W 14 L	1485	429	685	4381	140 A6 / 136 A8	2500	2240	2.0
16.9-30	12	TT	W 15 L	W 14 L	1485	429	685	4381	144 A6 / 140 A8	2800	2500	2.4
16.9-30	14	TT	W 15 L	W 14 L	1485	429	685	4381	146 A6 / 142 A8	3000	2650	2.8

MRT 330

18.4-30	8	TT	W 16 L	W 15 L	1545	460	711	4546	139 A6 / 135 A8	2430	2180	1.4
18.4-30	10	TT	W 16 L	W 15 L	1545	460	711	4546	145 A6 / 141 A8	2900	2575	1.8
18.4-30	12	TT	W 16 L	W 15 L	1545	460	711	4546	149 A6 / 145 A8	3250	2900	2.3
18.4-30	14	TT	W 16 L	W 15 L	1545	460	711	4546	151 A6 / 147 A8	3450	3075	2.6