



Salient Features

Multi-angled and bold lug-bars for service durability and self-cleaning.
 Suitably designed lug bar spacing for comfort drive & added traction.
 Strong and sturdy body plies for longer service durability.
 Tread contact patch with broader lugs for heavy duty prime-movers.

Applications

2WD Tractor

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE (bar)
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	
4.00-16	4	TT	3.00D	-	630	112	305	1880	69 A6 / 61 A8	325	257	3.4
4.50-16	4	TT	3.00D	-	655	122	305	1955	73 A6 / 65 A8	365	290	3.1
4.50-16	8	TT	3.00D	-	655	122	305	1955	78A6/70A8	425	335	4
5.00-16	4	TT	4.00E	-	680	140	335	2032	76 A6 / 69 A8	400	325	2.8
5.00-16	6	TT	4.00E	-	680	140	335	2032	84 A6 / 76 A8	500	400	4.2
6.00-16	6	TT	4.5 E	-	735	165	355	2220	88 A6 / 80 A8	560	450	3.3
6.00-16	8	TT	4.5E	-	735	165	355	2220	94 A6 / 86 A8	670	530	4.5
7.50-16	6	TT	5.5 F	-	820	205	370	2445	98 A6 / 90 A8	750	600	2.8
7.50-16	8	TT	5.5F	-	820	205	370	2445	103 A6 / 96 A8	875	710	3.7