MTF 284



Salient Features

Excellent load distribution during heavy loads.

Strong and sturdy body plies for longer service durability.

Excellent flotation and mobility from four rib design.

Tread contact patch with multi ribs for heavy duty prime-movers.

Applications

2WD Tractor	Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		INFLATION PRESSURE
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	(bar)
9.5L-15	6	TT/TL	7.0	8 LB	780	240	359	2330	99 A6 / 95 A8	775	690	2.5
9.5L-15	8	TT/TL	7.0	8 LB	780	240	359	2330	106 A6 / 102 A8	950	850	3.3
11L-15	8	TT/TL	8 LB	10 LB	795	279	380	2370	110 A6 / 106 A8	1060	950	3.0
11L-15	10	TT/TL	8 LB	10 LB	795	279	380	2370	114 A6 / 110 A8	1180	1060	3.6
10.00-16	8	TT/TL	8 LB	W 8 L	882	280	408	2625	115 A6 / 107 A8	1215	975	2.8
10.00-16	10	TL	8 LB	W 8 L	882	280	408	2625	119 A6 / 111 A8	1360	1090	3.9
11.00-16	8	TT/TL	10 LB	W 8, W 8 L	950	335	438	2820	118 A6 / 110 A8	1320	1060	2.5
11.00-16	10	TT/TL	10 LB	W 8, W 8 L	950	335	438	2820	122 A6 / 115 A8	1500	1215	3.1
11.00-16	12	TT	10 LB	W 8, W 8 L	950	335	438	2820	126 A6 / 123 A8	1700	1550	4.1
7.50-18	8	TT	5.5 F		874	208	405	2615	106 A6 / 98 A8	950	760	3.7