PRINCE 335



Salient Features

Low section flotation tyres offering high load capacity withminimum soil compaction.

Well Suited for both on and off road applications.

Applicable in high flotation and trailers.

Available with dual bead and reinforced side wall for extra load carrying capacity.

Applications

Forest Harvester	Forest Trailer	Trailer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD (LLV)		INFLATION PRESSURE	LI/SS	MAX. LOAD (HLV)		INFLATION PRESSURE
			REC.INCH	ALT.INCH						30KMPH (Kgs)	40KMPH (Kgs)	(bar)		30KMPH (Kgs)	40KMPH (Kgs)	(bar)
400/60-15.5	8	TL	AG13	–	874	404	380	2561	134A6/130A8	2120	1900	2.4	140A6/136A8	2500	2240	3.0
400/60-15.5	10	TL	AG13	–	874	404	380	2561	139A6/135A8	2430	2180	2.8	145A6/143A8	2900	2725	3.4
400/60-15.5	12	TL	AG13	–	874	404	380	2561	142A6/138A8	2650	2360	3.1	148A6/144A8	3150	2800	3.8
400/60-15.5	14	TL	AG13	–	874	404	380	2561	145A6/141A8	2900	2575	3.6	151A6/148A8	3450	3150	4.4
400/60-15.5	16	TL	AG13	–	874	404	380	2561	147A6/143A8	3075	2725	4.3	153A6/149A8	3650	3250	5.2
400/60-15.5	18	TL	AG13	–	874	404	380	2561	149A6/145A8	3250	2900	5.1	155A6/151A8	3875	3450	6.1