MR 500



Salient Features

Extra deep tread depth.

Excellent rib design for higher mileage.

Strong nylon casing for higher durability.

Excellent rib design for smooth steering.

Applications

Light Truck

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD SINGLE		INFLATION PRESSURE	LI/SS	MAX. LOAD DOUBLE		INFLATION PRESSURE
			REC.INCH	ALT.INCH						100KMPH (Kgs)	–	(bar)		100KMPH (Kgs)	–	(bar)
6.50-14	8	TT	4.5J	5J	703	176	316	2060	102J	850	–	–	100J	800	–	4.25
6.50-14	10	TT	4.5J	5J	703	176	316	2060	105J	925	–	–	103J	875	–	5.0
7.00-15	10	TT	5.5F	–	758	199	341	2235	110J	1060	–	–	105J	925	–	5.1
7.00-15	12	TT	5.5F	–	758	199	341	2235	114J	1180	–	–	109J	1030	–	6.2
7.00-15	14	TT	5.5F	–	758	199	341	2235	117J	1285	–	–	112J	1120	–	7.2
7.50-15	12	TT	6	6.5	780	211	351	2260	119J	1360	–	–	118J	1320	–	6.0
7.50-15	14	TT	6	6.5	780	211	351	2260	121J	1450	–	–	119J	1360	–	6.5
7.00-16	12	TT	5.5F	6.00G	784	199	353	2312	115J	1215	–	–	110J	1065	–	6.2
7.00-16	14	TT	5.5F	6.00G	784	199	353	2312	118J	1320	–	–	113J	1150	–	6.9
7.50-16	14	TT	6.00G	5.50F	813	211	366	2383	122J	1500	–	–	118J	1320	–	6.9
7.50-16	16	TT	6.00G	5.50F	813	211	366	2383	124J	1600	–	–	120J	1400	–	7.6
8.25-16	16	TT	6.50H	6.00G	854	234	384	2502	129J	1850	–	–	127J	1750	–	7.6
8.25-16	18	TT	6.50H	6.00G	854	234	384	2502	130J	1900	–	–	128J	1800	–	8.0