MR 518



Salient Features

Deep tread depth.

Excellent mileage and traction.

Multiple rib design for better steering control.

Better re-tread ability.

Applications

Light Truck

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD SINGLE		INFLATION PRESSURE	LI/SS	MAX. LOAD DOUBLE		INFLATION PRESSURE
			REC.INCH	ALT.INCH						100KMPH (Kgs)	–	(bar)		100KMPH (Kgs)	–	(bar)
6.00-14	6	TT	4.5J	4J	678	166	305	1980	93J	650	–	–	91J	615	–	3.25
6.00-14	8	TT	4.5J	4J	678	166	305	1980	98J	750	–	–	96J	710	–	4.25
6.50-14	8	TT	4.5J	5J	703	176	316	2060	102J	850	–	–	100J	800	–	4.25
6.50-14	10	TT	4.5J	5J	703	176	316	2060	106J	950	–	–	104J	900	–	5.30
6.50-15	12	TT	5.5F SDC	–	727	175	327	2134	109J	1030	–	–	107J	975	–	5.50
6.70-15	8	TT	5.0K	5.50F	724	180	327	2134	101J	825	–	–	97J	730	–	4.15
6.70-15	12	TT	5.0K	5.50F	724	180	327	2134	109J	1030	–	–	107J	975	–	5.50
7.00-15	12	TT	6	6.5	780	211	351	2260	120J	1400	–	–	118J	1320	–	6.00
7.00-15	14	TT	6	6.5	780	211	351	2260	121J	1450	–	–	119J	1360	–	6.48
6.00-16	10	TT	4.5E	–	748	166	337	2185	103J	875	–	–	99J	775	–	5.15
6.50-16	8	TT	4.5E	5K	771	175	347	2260	102J	850	–	–	98J	750	–	4.15
6.50-16	10	TT	4.5E	5K	771	175	347	2260	107J	975	–	–	102J	850	–	5.20
6.50-16	12	TT	4.5E	5K	771	175	347	2260	111J	1090	–	–	109J	1030	–	5.75
7.50-16	14	TT	6.00G	5.50F	813	211	366	2382	122J	1500	–	–	118J	1320	–	6.90
7.50-16	16	TT	6.00G	5.50F	813	211	366	2382	124J	1600	–	–	120J	1400	–	7.60