MG2 402



Salient Features

Good Traction in all weather conditions.

Good self-cleaning properties.

Strong and sturdy heavy duty nylon plies for longer service durability.

Cuts and cracks resistant tread compound for increased service life.

Applications

Backhoe	Dozer	Grader

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD	PRESSURE
			REC.INCH	ALT.INCH						(Kgs)	(bar)
13.00-24	12	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC)	1278	333	582.186	3785	143A8	2725	3.0
13.00-24	14	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC)	1278	333	582.186	3785	146A8	3000	3.5
13.00-24	16	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC)	1278	333	582.186	3785	148A8	3150	4
14.00-24	12	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	147A8	3075	2.8
14.00-24	14	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	151A8	3450	3.3
14.00-24	16	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	153A8	3650	3.8
14.00-24	20	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	157A8	4125	4
14.00-24	24	TL	8.00 TG SDC	9.00/1.5(DC), 10.00 VA (SDC),10.00WA(SDC)	1348	362	598	3962	160A8	4500	4.5