MG2 419



Salient Features

Good Traction in all weather conditions.

Good self-cleaning properties.

Strong and sturdy heavy duty nylon plies for longer service durability.

Cuts and cracks resistant tread compound for increased service life.

Applications

Backhoe	Dozer	Grader

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD	PRESSURE
			REC.INCH	ALT.INCH						(Kgs)	(bar)
15.5-25	12	TL	12.00/1.3	–	1270	384	572	3772	142 A8	2650	2.3
15.5-25	14	TL	12.00/1.3	–	1270	384	572	3772	145 A8	2900	2.7
15.5-25	16	TL	12.00/1.3	–	1270	384	572	3772	147 A8	3075	3.2
17.5-25	12	TL	14.00/1.5	–	1348	445	596	3938	145 A8	2900	2
17.5-25	14	TL	14.00/1.5	–	1348	445	596	3938	148 A8	3150	2.4
17.5-25	16	TL	14.00/1.5	–	1348	445	596	3938	150 A8	3350	2.8
20.5-25	16	TL	17.00/2.0	17.00/1.7	1492	520	671	4395	156 A8	4000	2.3
20.5-25	20	TL	17.00/2.0	17.00/1.7	1492	520	671	4395	160 A8	4500	2.8