ML2 455



Salient Features

Heavy duty side walls to give protection against damages.

Advance tread compound for long life on paved & other hard surface.

Special design for broadest contact surface & maximum gripping power.

Applications

Skidsteer

SIZES

SIZE	PR	TYPE	RIM		O.D (mm)	S.W (mm)	SLR (mm)	RC (mm)	LI/SS	MAX. LOAD		PRESSURE
			REC.INCH	ALT.INCH						10KMPH(Kgs)	15KMPH(Kgs)	(bar)
10-16.5	8	TL	8.25	–	780	263	356	2286	130 A2/122 A3	1880	1500	4.2
10-16.5	10	TL	8.25	–	780	263	356	2286	134 A2/126 A3	2120	1700	5.2
10-16.5	12	TL	8.25	–	780	263	356	2286	138 A2/130 A3	2375	1900	6.2
10-16.5	14	TL	8.25	–	780	263	356	2286	140 A2/132 A3	2500	2000	6.7
12-16.5	8	TL	9.75	–	825	314	381	2434	135 A2/127 A3	2180	1750	3.4
12-16.5	10	TL	9.75	–	825	314	381	2434	140 A2/131 A3	2500	1950	4.5
12-16.5	12	TL	9.75	–	825	314	381	2434	145 A2/137 A3	2900	2300	5.5
12-16.5	14	TL	9.75	–	825	314	381	2434	147 A2/139 A3	3075	2430	6.2